

REQ22/23

REQUISITION FORM FY22/23

DATE PREPARED: 6/21/2023
REQ. CONTACT PERSON: Gerald Bailey / Randy Loock
REASON: Additional Engine for Micanopy
VENDOR # OR NAME Hall-Mark RTC #1379
CONTACT & TEL Chris Beville Phone: 352-304-7362 Fax # 352-629-2018
EMAIL ADDRESS: chris.beville@revrtc.com
VENDOR ADDRESS: 725 S.W. 46th Ave. Ocala, FL 34474
SHIP TO: PW-WC-LA-ET (CIRCLE ONE)
DELIVER BY DATE: 09/30/2024

ITEM DESCRIPTION:

LINE #1: Tallahassee Contract # 3740A
(1) 2024 E-One Fire Pumper 4 Door, Typhoon
(See attached specifications and quote)

QTY.: 1.0
ORDER UOM: Each
UNIT COST: \$ 735,465.62 TOTAL REQ. AMT. \$ 735,465.62

ACCOUNT# 011.54.5480.522.64.00 #6235401

APPROVED:  6-21-23
ASST. PW DIRECTOR DATE

CAPITAL OUTLAY # _____

APPROVED: _____
DIRECTOR DATE

FISCAL ASST: _____
DATE

COMMENTS:

Color: Red & White
Additional Fire Engine for Micanopy
(See attached options)



E-ONE APPARATUS PROPOSAL


DATE: June 08, 2023


This Proposal has been prepared for:
Alachua County Public Works
5620 NW 120 Lane
Gainesville, FL 32653


Hall-Mark RTC. is pleased to offer Alachua County public works one (1) 2024 E-ONE Typhoon pumper to be custom built and equipped in accordance with the requirements of Alachua County Public Works Department to the attached truck list. This unit is quoted using the Tallahassee Contract #3740A The purchase price shall include all vehicle components and NFPA equipment as requested by the fire department as detailed in the Hall-Mark Proposal. Delivery will be F.O.B. Customer location and will be made approximately 870 calendar days. Terms of payment shall be cash on delivery (COD) when unit arrives at Alachua County Public Works Department.


E-ONE CUSTOM PUMPER-74221	\$ 490,710.00
Customer changes	\$ 244,755.62
Total	\$ 735,465.62

This quote is valid until 07/30, 2023.


Chris Beville - Account Manager
725 SW 46th Avenue, Ocala, FL 34474 (352) 304-7362


Date


Dee Daniels - Director of Sales
725 SW 46th Avenue, Ocala, FL 34474 (352) 629-6305


Date

Q125984 Rev 25



E-ONE APPARATUS PROPOSAL


DATE: June 08, 2023


This Proposal has been prepared for:
Alachua County Publics Works
5620 NW 120 Lane
Gainesville, FL 32653


Hall-Mark RTC. is pleased to offer Alachua County public works one (1) 2024 E-ONE Typhoon pumper to be custom built and equipped in accordance with the requirements of Alachua County Public Works Department to the attached truck list. This unit is quoted using the Tallahassee Contract #3740A The purchase price shall include all vehicle components and NFPA equipment as requested by the fire department as detailed in the Hall-Mark Proposal. Delivery will be F.O.B. Customer location and will be made approximately 870 calendar days. Terms of payment shall be cash on delivery (COD) when unit arrives at Alachua County Public Works Department.


E-ONE CUSTOM PUMPER-74221	\$ 490,710.00
Customer changes	\$ 244,755.62
Total	\$ 735,465.62

This quote is valid until 06,30, 2023.


Chris Beville – Account Manager
725 SW 46th Avenue, Ocala, FL 34474 (352) 304-7362


Date


Dee Daniels – Director of Sales
725 SW 46th Avenue, Ocala, FL 34474 (352) 629-6305


Date

Q113837 Rev 36



Fire Apparatus Quotation for:
ALACHUA CO.



Quotation Number: 125984 Rev: 25

Unit Description: PRAL-TYPN

Quote Description: Rescue Pumper, Aluminum, Typhoon

Salesperson: CBEVILLE

Salescode	Extended Description	Qty	
TESTING COMPLIANCE STANDARD			
1001-0017	Unit is part of a multiple order. Production order numbers are:	1	
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1	
1001-0100	Prior trucks for this customer include the following shop order(s):	1	
3090-0002	OAH. Unit has no overall height restrictions.	1	
3090-0004	OAL. Unit has no overall length restrictions.	1	
3090-0006	The hose bed is to have the capacity for the following hose. Hose load shall be listed from driver to officer.	1	Lay 1 - 600 ft. of 3.00 DJ Lay 2 - 1200 ft. of 5.00 LDH Estimated Weight - 1734 lbs.
3340-1137-12C	Equipment allowance on the apparatus shall be 2500 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1	
BUMPERS			
1160-0016	28" Front Bumper Gravel Shield Extension.	1	
1160-0140	3/16" diamond plate Front Bumper Gravel Shield for heavy duty bumper. Includes 1" turn down around perimeter of HD bumper.	1	
1160-0142	Front frame extensions to be drop style IPOS. Includes integral tow eyes below bumper.	1	
1160-0346	Heavy duty, formed, 12" front bumper with full wrap around. Corners to be tapered for an 8.5" wide mounting area. Includes support wings for outboard sides (as applicable). To be painted as specified.	1	
1160-0351-589	Bumper to be extended (boxed out) for mechanical siren to be recessed without intruding into the bumper trays, recessed crosslays or any other options as applicable. Location: center.	1	
BUMPER TRAYS			
1150-0147	Diamond plate lid for driver, center, and officer hose trays. 5.25" high with dual	1	

Salescode	Extended Description	Qty	
BRAKE SYSTEMS			
	axle. (Note: Brake chatter may occur while backing. This is a condition inherent with front S-Cam brakes.)		
1100-0002	ArvinMeritor 16-1/2" x 7" S-cam brakes with cast brake drums for a single rear axle.	1	
1100-0005	Brake system air 4X2/4X4.	1	
1100-0006	Parking brake release mounted on the driver's side lower dash.	1	
AIR SYSTEM OPTIONS			
1110-0000-181	Inlet for air system. Location: bumper and/or gravel shield driver's side.	1	
1110-0002	Air dryer Bendix AD-9.	1	
1110-0006	Air lines nylon.	1	
1110-0026	Air horns Hadley e-tone recessed in bumper (PR).	1	
ENGINES & TRANSMISSIONS			
1200-0017	Push-button transmission shift selector.	1	
1200-0021	TranSynd, Shell Spirax S6ATF A295, or equivalent synthetic transmission fluid for EVS4000 series.	1	
1200-0097	Electronic limiting of speed to 68 MPH maximum. Note: Axle gear ratio will be as low as possible while allowing for 68 MPH top speed to improve acceleration. Note: Max speed may be set at 65 MPH due to tire rating.	1	
1200-0421	Eng/Trans Cummins X12 455HP with EVS4000 transmission. 2021 EPA Compliant.	1	
SECONDARY BRAKING			
1125-0002	Jacobs engine compression brake. Note: Brake lights will illuminate when auxiliary brake is activated.	1	
1125-0023	Transmission to seek second gear when Jacobs engine brake or Telma retarder is engaged. N/A with Trans retarder.	1	
COOLING PACKAGE			
1800-0013	Cooling system for use with Typhoon, Cyclone and Quest chassis. For use with 2010 - 2021 EPA engines. Includes coolant recovery system.	1	
FUEL SYSTEMS			
1350-0005	Fuel system 65 gallons.	1	
1350-0012-670	Fuel shut-off valve. Location: one (1) inlet side of OEM fuel filter.	1	
1350-0022	Fuel line hose rubber.	1	
ALTERNATOR			

Salescode	Extended Description	Qty	
CAB DOOR OPTIONS			
1550-0285	Driver and officer door windows to be power actuated with HD regulators. Switches to be located at center dash. For use with new Typhoon and 100" wide Cyclone cabs.	1	
1550-0287	Cab doors to be barrier style. For use with new Typhoon and Cyclone only.	1	
1550-0377	All cab doors shall have exterior pull style handles with integral key lock (glass reinforced nylon).	1	
CAB STEP OPTIONS			
1640-0047	Lower steps to extend 3.5" past cab. For use with legacy Typhoon / Cyclone with barrier style doors and new Typhoon / Cyclone with barrier style or extended doors.	1	
MIRRORS			
1670-0001-274	Ramco 6001FFR mirrors. Remote controlled with top CAS750 manual convex. Location: mounted on front corners of cab.	1	
1670-0031	2" extension for Ramco mirrors.	1	
1670-0088	Driver and officer Ramco cab mirrors to be heated. Includes all surfaces (flat and convex, as applicable).	1	
MISC EXTERIOR CAB OPTIONS			
1550-0020	Windows cab side fixed driver's side.	1	
1550-0033	Windows cab side fixed officer's side.	1	
1675-0022	Pair of 18" handrails located just behind driver and officer front door one each side.	1	
1675-0023	Pair of 18" handrails located just behind driver and officer rear door (ALS doors if equipped) one each side.	1	
1675-0030	Mud flaps, front, black with E-ONE logo.	1	
1675-0038-000-18	Sign plate smooth 30" x 30" mounted on cab roof (vista if equipped). Color: FLNA 4006 E-ONE WHITE.	1	
1675-0040	Body and cab mud flap heights. Bottom of flaps to be approx. 12" off ground.	1	
1675-0047	Rear cab wall to be 3/16" aluminum diamond plate.	1	
1675-0201	Large radius cab wheel well. Includes bolt-on adjustable wheel well trim.	1	
HVAC			
1515-0048	Controls for heating and air conditioning shall be located in the driver side lower dash area. For use without front air bags only.	1	
1515-0099	Air conditioning with radiator mounted condenser for use with Cummins L9 and X12 engine. Includes reduced profile evaporator w/powder coated cover and	1	

Salescode	Extended Description	Qty	
MISC INTERIOR CAB OPTIONS			
1685-0669	Severe duty dash package with low profile center section. Cast alum construction. Includes smooth plate alum lower kick panels; all painted to match cab interior.	1	
1685-0692	Cab insulation package. Includes insulation for ceiling, front wall, rear wall, side walls, below seat risers and in doors.	1	
1685-0891	Cab interior padding to be gray.	1	
CAB ELECTRICAL OPTIONS			
1750-0024-181-04	Auto-Eject receptacle inlet 20 amp located bumper and/or gravel shield driver's side with a Yellow cover.	1	
1750-0032	Switch horn button three position DOT/air horn/electronic siren.	1	
1750-0046-195	Cab Headlights. Position: lower.	1	
1750-0072-546	12 VDC electrical outlet wired battery hot. Location: In cab officer side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1	
1750-0072-593	12 VDC electrical outlet wired battery hot. Location: officer side dash.	1	
1750-0073-585	Antenna base Tessco P/N 90942 (NMO Motorola Style - also called MATM style) on cab roof. Location: driver side forward with coaxial cable terminating at the center of the dash board.	1	
1750-0073-587	Antenna base Tessco P/N 90942 (NMO Motorola Style - also called MATM style) on cab roof. Location: officer side forward with coaxial cable terminating at the center of the dash board.	1	
1750-0075	English dominant main cab gauge cluster.	1	
1750-0198-A31	Battery charger to be located behind driver's seat.	1	
1750-0265	Speedometer for officer side multiplex display.	1	
1750-0343	Battery charger E-ONE LPC 20. 120 volt inlet, 20 amp output. Includes status indicator panel.	1	
1750-0447	Dome Lts Red/White Whelen model 60CREGCS LED. Package includes two lights mounted in the front and two mounted in the rear of the cab. White light wired through door and light assembly switch. Red light through light assembly switch.	1	
1750-0449	Momentary DPF regeneration override switch.	1	
1750-0482	Control push-button switch officer switch panel for Q2B siren.	1	
1750-0485	Control push-button switch officer switch panel for air horns.	1	
1750-0554	FireTech LED cab headlights.	1	
1750-0582	Light EON LED (EA) mounted in bench seat riser. The light(s) shall be wired through the compartment door switch(s) or rocker switch as applicable if equipped with cargo nets.	1	

Salescode	Extended Description	Qty	
COVERS			
3305-0002	Bi-Fold diamond plate cover for the crosslay area. Includes applicable grab handles and (2) hold downs.	1	
3305-0004	Crosslay cover to be hinged forward.	1	
3305-0022-000-02	Vinyl rear cover for diamond plate hose bed cover. Color: Red.	1	
3305-0024-000-02	Vinyl Red side covers for diamond plate crosslay cover.	1	
3305-0083	(4) piece aluminum hose bed cover. Includes dividerless cross structure, fill tower(s) access door(s) and handles (as applicable), (2) gas shocks, positive hold-opens/hold-closed at center and at the rear, (6) grab handles- (4) fwd cover and (2) fwd area of rear cover with (2) hand rails on rear cover. A landing platform (sized and positioned as required with overall rear end configuration) with embossed diamond plate surface will be centrally located at the upper rear of the apparatus to assist with hose bed cover operations.	1	
3305-0119	Hold open device(s) for aluminum crosslay (single or bi-fold) cover. Locate as required based off options on module.	1	
PUMP MODULE			
3130-0167	Pump module to be 76" wide (side to side). Includes upper, lower, crosswalk, speedlay and tranverse module(s) if applicable.	1	
3130-0523	Side mount pump module. Extruded aluminum with runningboards.	1	
3130-0534	Pump panel opening is 51" wide.	1	
3130-0540	Pump module height is 80". Pumper / tanker only.	1	
3136-0214	Crosslay triple 7.75/7.75/10" wide double stack to hold up to 200' of 2.0" DJ (each) in front lays and 200' of 2.5" DJ hose in rear lay.	1	
PUMP PANELS			
3134-0016	Stainless steel driver and officer side pump panels.	1	
3134-0055	Officer side upper pump access panel to be horizontally hinged with stainless steel door. Includes (2) push button latches and (2) hold open devices.	1	
3134-0064	The gauge panel(s) on the driver side of the Side Mount module to be hinged upward. Panel(s) to include (2) mechanical/pneumatic (as applicable to panel size) hold opens and latches.	1	
MISC PUMP PANEL OPTIONS			
4460-0003	Pump panel tags color coded per NFPA compliance.	1	
4460-0088-282	Air outlet with Innovative Control 1/4" valve w/1/4 turn "T" handle and label for: driver's side pump panel.	1	
PUMP MODULE OPTIONS			

Salescode	Extended Description	Qty	
HANDRAILS / STEPS			
3330-0277	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on driver side rear of the body. (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on driver side upper hosebed side (as applicable).	1	
3330-0278	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on officer side rear of the body. (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on officer side upper hosebed side (as applicable).	1	
3330-0279-060	Innovative Controls dual lighted LED folding step. Location: officer side front compartment face. Each location requires a minimum of (1) handrail per NFPA.	4	
MISC BODY OPTIONS			
3340-0004	Hosebed above the booster tank. Includes forward hosebed and tower(s) cover plate work (as applicable). Hosebed adjustable divider extrusion in the forward area and rearward area of the hose bed to run full width of the hosebed (as is practical with other hosebed mounted equipment).	1	
3340-0015	Diamond plate single axle wheel well. Includes bolt-on composite wheel well liners and aluminum trim fenderettes.	1	
3340-0058	Recessed fuel fill driver side wheel well.	1	
3340-0062	Divider medium. To run full length of hose bed (front to rear) behind single fill tower.	1	
3340-0075	Body mainframe and hosebed side assemblies for a 90" high body.	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0110	The rear of each hose bed divider to have a hand hold cut-out(s).	1	
3340-0145	Rub rail for the body and pump area module(s).	1	
3340-0405	Sign, "STAY BACK 500 FEET" with black reflective lettering. Locate below rear of body.	1	
3340-0681	Body mainframe layout line to be 24". Includes body and all applicable modules.	1	
SCBA BOTTLE STORAGE			
3320-0100	Strap, loop style to retain SCBA bottle(s). Locate one per bottle in each exterior body storage compartment.	1	
3320-0182-497	E-ONE designed (1) SCBA bottle storage driver side rear wheel well offset rearward with hinged door and push button latch. Door material to match wheel well material. Holds standard size SCBA bottle, 20lbs ABC Extinguisher (10.25"x7"x24") or 2.5 gal Water Extinguisher (9"x7"x24.5"). Door shall cover the recessed fuel fill if located in the wheel well adjacent to the SCBA storage.	1	

Salescode	Extended Description	Qty	
INTAKES			
4440-0006	2.5" Right intake Akron manual valve.	1	
INTAKE OPTIONS			
4445-0009	Intake relief valve, Akron.	1	
DISCHARGES AND PRECONNECTS			
4415-0008	1.5" Front bumper discharge Akron manual valve.	1	
4415-0012-654	1.5" Crosslay with Akron manual valve. Location: crosslay 1 & 2.	2	
4415-0022-350	2.5" Left Rear Discharge Akron Manual Valve. Location: left rear discharge.	1	
4415-0041	3" Deck Gun Discharge, Akron manual valve. (outlet shall terminate with MNPT threads unless extend gun is install)	1	
4415-0058-655	2.5" Crosslay Akron Manual Valve. Location: crosslay 3.	1	
4415-0161-581	2.5" Left Panel Discharge Akron Manual Valve w/30 Degree Chrome Droop. Location: left side discharge 1 .	1	
4415-0161-582	2.5" Left Panel Discharge Akron Manual Valve w/30 Degree Chrome Droop. Location: left side discharge 2 .	1	
4415-0164-584	2.5" Right Panel Discharge Akron Manual Valve w/30 Degree Chrome Droop. Location: right side discharge 2 .	1	
4415-0176-211	Brass Swivel in Tray officer side front bumper for Front Bumper Discharge.	1	
4415-0421-583	4" Pump Panel Discharge Akron Valve Handwheel Control. (Waterous pumps noted location to be forward lower port .) Location: right side discharge 1 .	1	
4417-0106-L65	Deck gun piping to be positioned centered in deck gun channel.	1	
DISCHARGE OPTIONS			
4417-0175	Innovative Controls push/pull valve controls with locking T handles.	1	
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	10	
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel .	1	
4417-0246	Dealer/Customer installed monitor, nozzle and/or tips, make and model as specified.	1	
PRESSURE GOVERNORS			
4465-0028	Class 1 Sentry pressure governor/ Twister throttle. Includes master intake and discharge gauges , water, oil, tran, volt and tachometer.	1	
GAUGES			
4435-0256-528	Innovative Controls SL Plus series tank gauge w/SL Plus Monster tank level	1	

Salescode	Extended Description	Qty	
WARNING LIGHTS			
	equipped. (Split light head(s) containing "white" light(s) are for additional or non-NFPA warning lights only - NOT for use in a NFPA compliant package.) Note: ION-T Series light only available with clear lenses.		
5600-0671-742-4T	Warning light Whelen ION-T Series model TLI Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side in pump module rubrail if equipped. (Split light head(s) containing "white" light(s) are for additional or non-NFPA warning lights only - NOT for use in a NFPA compliant package.) Note: ION-T Series light only available with clear lenses.	1	
5600-0789-3RF-4T	Warning/ground light Whelen M6V2 series Linear Super LED (PR). Location: (1) each side NFPA/ULC required lower zone forward side facing, color will be RED with CLEAR lenses.	1	
5600-0789-3RG-4T	Warning/ground light Whelen M6V2 series Linear Super LED (PR). Location: (1) each side NFPA/ULC required lower zone midship side facing, color will be RED with CLEAR lenses.	1	
5600-0789-3RH-4T	Warning/ground light Whelen M6V2 series Linear Super LED (PR). Location: (1) each side NFPA/ULC required lower zone rear side facing, color will be RED with CLEAR lenses.	1	
5600-0789-460-4T	Warning/ground light Whelen M6V2 series Linear Super LED (PR). Location: (1) each side of cab centered over wheel well, color will be RED with CLEAR lenses.	1	
5600-0947-457-4T	Warning light Whelen Rota-Beam series model 6RB* Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side of body rear facing up high.	1	
5600-0958-3RE-4T	Warning light Whelen 600 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone front facing.	1	
5600-0958-3RF-4T	Warning light Whelen 600 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone forward side facing.	1	
5600-0958-3RG-4T	Warning light Whelen 600 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone midship side facing.	1	
5600-0958-3RH-4T	Warning light Whelen 600 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone rear side facing.	1	
5600-0958-3RI-4T	Warning light Whelen 600 series Super LED (PR). Color: RED with CLEAR lenses. Location: (1) each side NFPA/ULC required lower zone rear facing.	1	
5600-0958-467-2Y	Warning light Whelen 600 series Super LED (PR). Color: AMBER with CLEAR lenses. Location: (1) each side above tail lights.	1	
DIRECTIONAL LIGHT BARS			
3340-0125	Smooth plate sanded box for recessed directional light bar on rear body.	1	
5310-0017	Whelen Traffic Advisor model TAL65 LED - 36" long.	1	
5310-0020-170	Directional light bar control is to be located center overhead.	1	

Salescode	Extended Description	Qty	
LIGHTS - DECK AND SCENE			
	body.		
5390-0334-397	FireTech FT-GSMJR scene lights (PR) with chrome flange and weatherproof connectors. Switch in cab (driver and officer side lights switched separately). Locate: (1) each side of cab, rearward of forward doors, up high.	1	
LIGHTS - NON-WARNING			
5400-0003	Engine compartment light (EA).	1	
5400-0150	Pump panel LED light package for side mount. Includes (6) Tecniq EON lights with S/S housings located (3) ea side. Includes S/S light shields (as applicable with intermediate steps).	1	
5400-0185	LED pump compartment light (EA).	1	
5400-0219-202	EON LED pump panel light - additional (EA). Location: driver side pump panel.	1	
5400-0219-203	EON LED pump panel light - additional (EA). Location: officer side pump panel.	1	
CONTROLS / SWITCHES			
5100-0000-198	Foot switch to control air horns located driver's side.	1	
5100-0001-1ME	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: officer's side overhead console for front cab brow lights.	1	
5100-0001-39T	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: driver rear of body for rear scene lights.	1	
5100-0001-3QG	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: officer's side overhead for officer's side 12V cab scene lights.	1	
5100-0001-3QH	Switch circuit three way. Includes (1) additional switch. An additional switch required for more than two locations. Location: officer's side overhead for driver's side 12V cab scene lights.	1	
5100-0006-198	Foot switch to control Q2B located driver's side.	1	
5100-0036-1N1	Additional programming instructions: side facing V series (or CZ series as applicable) scene lights wired through turn signals and ground light circuit.	1	
5100-0036-2JA	Additional programming instructions: the scene light portion of all side facing M6V lights to activate with reverse.	1	
5100-0036-4S6	Additional programming instructions: as specified. Per added note per customer specification.	1	
5100-0036-5CJ	Additional programming instructions: cab side facing M6V lights wired through cab door ajar light circuit.	1	

Salescode	Extended Description	Qty	
LIGHTS - AREA			
	switch in cab (driver and officer side facing lights switched separately). Location: driver and officer side over rear cab door.		
5450-0631-063	Light Whelen 12V Pioneer Plus flood LED model PFH1 powder coated white with external bottom raise pole. Includes switch accessible to driver. Location(s): officer side back of cab.	1	
5450-0631-064	Light Whelen 12V Pioneer Plus flood LED model PFH1 powder coated white with external bottom raise pole. Includes switch accessible to driver. Location(s): driver side back of cab.	1	
RECEPTACLES			
5470-0004-664	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: L2 high on forward wall.	1	
5470-0004-743	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: L3 high on forward wall.	1	
5470-0004-744	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: R1 high on forward wall.	1	
MISC LOOSE EQUIPMENT			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	
EXTERIOR PAINT			
8100-0089	All applicable pump/pre-connect application modules are to have a sanded finish (not painted job color). Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.	1	
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	
8100-0176-000-29	Paint E-ONE chassis cab - Sikkens paint (non-metallic color). Color: FLNA 3284 E-ONE RED.	1	
8100-0182-000-29	Paint Body - Small - For Pumpers, Rear Mounts, S/A Tankers/Wetsides and Rescues. Sikkens paint (non-metallic color). Color: FLNA 3284 E-ONE RED.	1	
8100-0186-000-39	Paint exterior surface of outer steel wheels. Sikkens paint. Color: Job Color.	1	
INTERIOR PAINT			
8150-0011	The interior of the cab to be painted multi-tone gray finish.	1	
STRIPING			
8300-0001	NFPA required reflective striping to be dealer/customer applied.	1	

Salescode	Extended Description	Qty	
WARRANTY / STANDARD & EXTENDED			
	(RFW0710).		
9100-0151	Frame Rail Corrosion (Zinc Plate and Powder Coat) Twenty Five (25) Years or 150,000 Miles Limited Warranty (RFW0316).	1	
9100-0165	Frame Rail Lifetime (50) Years or 250,000 Miles Limited Warranty (RFW0305).	1	
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS			
9300-0009	Manuals, Operator and Service in digital format.	1	
9300-0012	Pump panel approval drawings. Will be provided on purchased units prior to construction.	1	
9300-0016	Approval Drawings-Standard.	1	
9300-0031	Dash/Console panel layout approval drawings. Will be provided on purchased units prior to construction.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	
Dealer Supplied Equipment			