

DIMENSIONS ARE APPROXIMATE
 OVERALL HEIGHT = 106.5"
 OVERALL WIDTH WITH RUB
 RAILS & FENDERETTES = 98"

(7) WHELEN 900 SUPER LED WARNING LIGHTS
 RED/RED/RED/WHITE/RED/RED/RED
 WITH CLEAR LENSES

(5) TECNIQ S330 AMBER
 MINI-LED MARKER LIGHTS

OEM POWER
 ADJUSTABLE
 MIRRORS

FLASHING HEADLIGHTS W/
 DAYTIME RUNNING LIGHTS

(2) WHELEN 500 SERIES
 RED SUPER LED GRILLE
 LIGHTS IN CPI HOUSINGS
 WITH CLEAR LENSES

(2) WHELEN SA315 SERIES
 SIREN SPEAKERS BEHIND
 GRILLE AREA

HIDDEN UNLOCK SWITCH
 IN GRILLE AREA

THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
 DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.

MODEL YEAR 2025



FRONT EXTERIOR VIEW
 CHIEF XL-III/FORD E-450 CHASSIS-GAS ENGINE

DATE:
 4-7-22
 DWG.
 TKD
 DATE:

DRAWING NO.
 REV.
 NR
 CHIEFXL-1

APPROVAL SIGNATURE:

DIMENSIONS ARE APPROXIMATE
 OVERALL HEIGHT = 106.5"
 OVERALL WIDTH WITH RUB
 RAILS & FENDERETTES = 98"

(5) TECNIQ S330 RED
 MINI-LED MARKER LIGHTS

LED LICENSE
 PLATE LIGHT

WHELEN 900 AMBER SUPER LED WITH CLEAR LENS

(2) WHELEN 900 24-DIODE LED LOAD LIGHTS

(2) WHELEN 900 RED
 SUPER LED WITH
 CLEAR LENSES

REAR VIEW CAMERA

(2) WHELEN 900 RED
 SUPER LED WITH
 CLEAR LENSES

(1) EACH SIDE, WHELEN
 600 LED BRAKE/TAI,
 600 LED TURN
 600 LED BACK-UP

INDEPENDENT BUMPER WITH
 NON-SKID FLIP-UP CENTER
 STEP AND COT PROTECTOR
 ON STEP EDGE. TOW HOOKS
 LOCATED BELOW STEP/BUMPER.

THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
 DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.

MODEL YEAR 2025



REAR EXTERIOR VIEW
 CHIEF XL-III/FORD E-450 CHASSIS

DATE:
 4-7-22
 DWG. TKD REV. NR

DRAWING NO.
 CHIEFXL-2

DIMENSIONS ARE APPROXIMATE
 OVERALL HEIGHT = 106.5"
 OVERALL LENGTH = 272.75"
 MODULE LENGTH = 169"

TECNIQ S330 RED MINI-LED MARKER
 LIGHT TO ALSO FLASH WITH TURN SIGNAL


(2) WHELEN 900 RED SUPER LED
 WARNING LIGHTS WITH CLEAR LENSES

(2) WHELEN 900 24-DIODE LED SCENE LIGHTS

KUSSMAUL 20 AMP
 SUPER AUTO-EJECT
 SHORELINE INLET

WHELEN 700 RED SUPER
 LED WITH CLEAR LENS
 IN TILT HOUSING

EXHAUST VENT



NON-SKID RUNNING
 BOARD SURFACE

SUCTION
 PUMP

WHELEN 700 RED SUPER
 LED WITH CLEAR LENS

COMPARTMENT
 O.S.S #1

CLEAR OPENING: 70.00h x 18.25w
 INSIDE DIM'S.: 79.75h x 24.50w x 20.75d
 MAIN OXYGEN STORAGE

O.S.S #2

CLEAR OPENING: 37.50h x 38.50w
 INSIDE DIM'S.: 40.50h x 44.00w x 20.75d
 (1) ADJUSTABLE SHELF

O.S.S #3

CLEAR OPENING: 58.50h x 30.75w
 INSIDE DIM'S.: 60.25h x 34.50w x 20.75d
 INSIDE/OUTSIDE ACCESS
 (1) ADJUSTABLE SHELF

THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
 DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.

MODEL YEAR 2025




STREETSIDE EXTERIOR VIEW
 CHIEF XL-III/FORD E-450 CHASSIS

DATE:
 4-7-22
 DWG. TKD
 REV. NR

DRAWING NO.
 CHIEFXL-3

DIMENSIONS ARE APPROXIMATE
 OVERALL HEIGHT = 106.5"
 OVERALL LENGTH = 272.75"
 MODULE LENGTH = 169"



COMPARTMENT
 O.S.S #4

CLEAR OPENING: 68.00h x 24.75w
 INSIDE DIM'S. 4A: 77.75h x 15.00w x 20.75d
 BACKBOARD/SCOOP STORAGE
 INSIDE DIM'S. 4B: 77.75h x 13.50w x 20.75d
 (2) ADJUSTABLE SHELVES WITH INSIDE/OUTSIDE ACCESS

O.S.S #5

CLEAR OPENING: 46.75h x 17.25w
 INSIDE DIM'S.: SEE PARTITION INTERIOR VIEW
 INSIDE/OUTSIDE ACCESS WITH (3) ADJUSTABLE SHELVES

THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
 DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.


MODEL YEAR 2025



CURBSIDE EXTERIOR VIEW
 CHIEF XL-III/FORD E-450 CHASSIS

DATE:
 4-7-22
 DWG. TKD
 REV. NR

DRAWING NO.
 CHIEFXL-4



COMPARTMENT

#1 DOOR OPENING: 11.75h x 31.50w
 INSIDE DIMS: 13.25h x 33.00w x 17.25d
 (1) ADJ SHELF EACH SIDE OF CENTER DIVIDER
 SLIDING POLYCARBONATE DOORS
 TOTAL CABINET WEIGHT RATING = 25 lbs.

#2 DOOR OPENING: 11.75h x 45.00w
 INSIDE DIMS: 13.25h x 46.50w x 17.25d
 (1) ADJ SHELF EACH SIDE OF CENTER DIVIDER
 SLIDING POLYCARBONATE DOORS
 TOTAL CABINET WEIGHT RATING = 25 lbs.

#3 DOOR OPENING: 26.50h x 28.75w
 INSIDE DIMS: O.S.S. #3
 HINGED POLYCARBONATE DOORS WITH FULL LENGTH HANDLES AND CENTER SQUEEZE LATCHES
 TOTAL CABINET WEIGHT RATING = 40 lbs.

#4 DOOR OPENING: 12.50h x 12.25w
 INSIDE DIMS: 14.00h x 13.75w x 17.25d
 (1) ADJUSTABLE SHELF
 SLIDING POLYCARBONATE DOORS
 TOTAL CABINET WEIGHT RATING = 15 lbs.

#5 PULL-OUT DRAWER WITH HINGED ACRYLIC WRITING SURFACE
 INSIDE DIMS: 4.50h x 14.50w x 13.25d
 LOCKING STAINLESS STEEL FLUSH PULL LATCH
 TOTAL DRAWER WEIGHT RATING = 10 lbs.

THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
 DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.


MODEL YEAR 2025



STREETSIDE INTERIOR VIEW
 CHIEF XL-III

DATE: 4-7-22
 DWG. TKD
 REV. NR

DRAWING NO. CHIEFXL-5



COMPARTMENT

#1 DOOR OPENING: 30.00h x 7.25w
 INSIDE/OUTSIDE ACCESS TO OSS #4B
 HINGED POLYCARBONATE DOOR WITH FULL LENGTH
 HANDLE AND CENTER SQUEEZE LATCH
 TOTAL CABINET WEIGHT RATING = 25 lbs.

#2 INSIDE DIM'S: 14.25h x 72.00w x 21.00d

THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
 DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.


MODEL YEAR 2025



CURBSIDE INTERIOR VIEW
 CHIEF XL-III

DATE: 4-7-22
 DWG. TKD
 REV. NR

DRAWING NO.
 CHIEFXL-6



COMPARTMENT

#1 DOOR OPENING: 15.00h x 25.75w
 INSIDE DIMS: 16.50h x 27.25w x 17.00d
 (1) ADJUSTABLE SHELF
 SLIDING POLYCARBONATE DOORS
 TOTAL CABINET WEIGHT RATING = 25 lbs.

#2 DOOR OPENINGS: 21.25h x 25.75w
 INSIDE DIMS: 24.75h x 31.50w x 20.75d
 HINGED POLYCARBONATE DOORS WITH FULL LENGTH
 HANDLES AND CENTER SQUEEZE LATCHES
 (1) ADJUSTABLE SHELF PER COMPARTMENT
 TOTAL CABINET WEIGHT RATING = 60 lbs. EACH

#3 VENTED RADIO CABINET
 INSIDE DIMS: 9.00h x 11.75w x 19.50d
 HINGED ALUMINUM DOOR
 CHROME LOCKING LEVER LATCH
 TOTAL CABINET WEIGHT RATING = 20 lbs.

THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
 DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.


MODEL YEAR 2025



PARTITION INTERIOR VIEW
 CHIEF XL-III

DATE:
 4-7-22
 DWG.
 TKD

DRAWING NO.
 REV.
 NR
 CHIEFXL-7



THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
 DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.

MODEL YEAR 2025



REAR INTERIOR VIEW
 CHIEF XL-III

1:12

DATE:	4-7-22
DWG.	REV.
TKD	NR

DRAWING NO.
CHIEFXL-8

RECESSED SHARPS/TRASH WITH HINGED
ACRYLIC LID BELOW SEPARATE BENCH LID

(8) LED
DOME LIGHTS

BACKBOARDS
SCOOP

96" GRAB RAIL

PDQ
CAB'T

ACP PROFILE

 = (2) RECESSED CEILING IV HANGER LOCATIONS

 = (1) CEILING OXYGEN OUTLET

* (2) ANTENNA BASES LOCATED OUTBOARD OF
DOME LIGHTS WITH COAX SERVICE LOOP

96" FERNO STAT-TRAC CENTER MOUNT COT HARDWARE

MODULE WIDTH = 96"
MODULE LENGTH = 169"
MODULE HEAD ROOM = 72"

THIS DRAWING IS FOR REPRESENTATIONAL PURPOSES ONLY. DETAILS ARE CONCEPTUAL AND ARE SUBJECT TO CHANGE DURING DESIGN AND CONSTRUCTION
DIMENSIONS ARE APPROXIMATE UNLESS NOTED OTHERWISE TO MEET A SPECIFIC CUSTOMER NEED.

MODEL YEAR 2025



FLOOR INTERIOR VIEW
CHIEF XL-III

DATE:
4-7-22
DWG. TKD

REV.
NR

DRAWING NO.
CHIEFXL-9



Quotation Summary

Florida Sheriff's Association Braun Proposals 2023-01-12 14-10-09

Reference: QUO0000007848 **Rev:** 0
Purchaser: Ten-8 Fire Equipment, Inc.
Contact: Cindy Morgan
Address: 2904 59th Ave. Dr. East

Brandenton, FL
 USA

Telephone:

Opportunity: Florida Sherrif's Association
Account: Florida Sheriff's Association
Contact: Cindy Morgan
Shipping Address:

Currency: USD
Quotation Date: 2023-01-12
Expiration: 2023-02-11

Sales Contact: Eric Wilcox
Mobile: 4196158839
Phone:

Factory Contact: Chuck Burgess
Mobile: 4196517924

Name	Specifications
Chief XL Type III	-72" Headroom -169"L Full Seam Welded Module



Sales Options by Category

Braun - KKK Change Notice		
Item Number	Description	Quantity
00-01-0001	GENERAL CONDITIONS	1.00
00-01-0006	DYNAMIC SIDE IMPACT & ROLLOVER TESTS	1.00
00-01-0017	BIDDER IS KKK-A-1822F AMENDMENT 1 COMPLIANT	1.00
80-10-0000	KKK-A-1822F COMPLIANCE PACKAGE KKK-A-1822F compliance sticker, electrical load analysis sticker, and payload sticker shall be installed in the oxygen compartment. Any deviations from KKK-A-1822F shall be listed in the vehicle delivery packet with a notation on the-compliance sticker.	1.00
00-01-0029	NO CONTRACT REQUIRED	1.00



NO STS, HGAC, FSA, SOURCEWELL or GPO contract required		
00-01-0053	NO BOND REQUIRED No Bond is Required	1.00

Braun - Chassis

Item Number	Description	Quantity
00-01-0040	Administration Fee	1.00
00-01-0081	SURCHARGE FEE	1.00
25XLE450	TYPE III - AMBULANCE - CHIEF XL III E450 - 72 INCH INTERIOR HEADROOM 2025 Chief XL Type III - 169" Module - 72" Interior Headroom. Manufactured in Van Wert, Ohio, USA.	1.00
CH_E2450L	CHASSIS - FORD E450 158" WB 4X2 DRW (100 C.A.) GAS ENGINE Ford E-450 Cutaway Chassis, 158" WB 4x2 DRW (100 C.A.) Gas Engine	1.00
15-00-0010	FUEL TANK - FULL UPON FACTORY RELEASE The chassis fuel tank of the completed unit shall be full at time of release from the ambulance manufacturer's facility.	1.00
20-10-0603	ENGINE BLOCK HEATER - OEM PLUG An engine block heater shall be included in the chassis with the 125 VAC power cord.	1.00
20-20-0252	HEAT SHIELDS, PROTECTIVE Install: aluminized steel protective heat shields to the upper laterals above the exhaust system.	1.00
20-20-0277B	HIGH IDLE SYSTEM - B A high-idle module will be added to the chassis. The high idle will be engaged automatically by the M-Tech system when all chassis parameters are met. Chassis parameters include but not limited to vehicle in park, service brake not depressed, accelerator not depressed, parking brake set and battery voltage. High-idle may also be activated by the M-Tech heat or A/C.	1.00
20-10-0203	BATTERY - TWO SYSTEM - E SERIES GAS CHASSIS The vehicle shall have a two (2) battery, 12-volt system rated at 1500 cold cranking amps (CCA). One battery will be securely installed in a slide out drawer, located on the lower right front of the module. The second battery shall be installed under the chassis hood.	1.00
20-23-0101	FLOOR CONSOLE E450 STANDARD CONSOLE - ALUMINUM PLEASE NOTE: Console drawings are for reference only and do not include all features depicted on the drawings. All consoles shall be designed, priced, and approved internally to allow for accurate BOM pricing. The prices shown are estimated for general budget pricing only and pricing is subject to design; must contact manufacturer for pricing validation.	1.00
30-10-0030	BACKUP ALARM	1.00



	Install: (OSHA approved) back up alarm with a disable control for silent backing, located on the MCC (master control console).	
20-30-0804	RUNNING BOARDS - STAR PUNCHED DIAMOND PLATE Flared aluminum diamond plate running boards with a star punched non-skid surface shall be provided on the cab.	1.00
20-30-0201	MIRRORS, EXTERIOR OEM MANUAL TELESCOPING- REMOTE WITH/CONVEX	1.00
20-30-0261	OEM AUTO-LOCK DISABLED (cab & module doors do not auto lock or unlock) The OEM auto-lock feature will be disabled.	1.00
30-10-0753	SIREN, WHELEN 295-HFSA7-REMOTE WITH MICROPHONE (Meets CA Title 13) A Whelen 295-HFSA7 remote dual siren amplifier shall be flush-mounted in the master control console located in the cab. The siren shall be capable of hands-free operation and shall be equipped with a noise canceling microphone. (Meets CA Title 13)	1.00
30-10-0809	SIREN SPEAKERS, WHELEN SA315 - BEHIND THE GRILLE Install: Whelen dual 100-watt siren speakers shall be installed behind the grille area.	1.00
20-40-0206-10	WHEEL SIMS - STAINLESS WITH VALVE STEM EXTENSIONS - E SERIES CHASSIS Provide: Stainless steel full wheel simulators for the front and the outside rear wheels, Air Max valve extensions provided to properly inflate the inner dual rear tires.	1.00

Braun - Electrical

Item Number	Description	Quantity
30-06-0004	ELECTRICAL SYSTEM - WELDON V-MUX, MICRO PROCESSOR BASED Install: Weldon V-MUX 100% solid state microprocessor based multiplex system.	1.00
30-10-0110	ELECTRICAL CIRCUITS All electrical circuits: shall have wiring and circuit protection suitable to the demand and must meet the national electric code (NEC) wiring requirements, added on wiring (18 GA through 10 GA) color coded and stamped with code numbers for easy identification, SLX high temperature thermoplastic cross link wire used. SGX insulated cable used for all under hood / underbody battery and charging system cable. High temperature (375° f) thermoplastic loom used on all harnesses.	1.00
30-06-0126	ELECTRICAL COMPARTMENT (PDQ) - MULTIPLEX ELECTRICAL SYSTEM Electrical compartment / hinged door w/ (2) chrome locking lever latches/ located on the partition wall behind the attendant seat.	1.00
30-06-0325	FLASHER - MULTIPLEX ELECTRICAL SYSTEM Provide: Flasher within and programmed by the multiplex electrical system.	1.00
30-06-0350	FLASHING HEADLIGHTS - MULTIPLEX ELECTRICAL SYSTEM	1.00



Headlights (high beams) shall be programmed through the multiplex system to alternate flash (wig-wag).

30-10-0190	<p>GROUND FAULT CIRCUIT INTERRUPTER-GFCI</p> <p>Install: A 125 VAC, 20 AMP circuit breaker with ground fault circuit interrupter (GFCI) electronic ground leakage detection in the load center for the shoreline circuit.</p>	1.00
30-06-0285	<p>MODULE DISCONNECT - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Install: In-Power disconnect to keep the system power engaged after the ignition is switched to the "off" position.</p>	1.00
30-06-0575	<p>REVERSE -TRANSMISSION- FUNCTIONS - MULTIPLEX ELECTRICAL SYSTEM</p> <p>System programmed to provide activation for: rear outboard warning lights, rear side warning lights, rear scene lights, the rear side scene lights - when the transmission selector lever is placed into "reverse" position.</p>	1.00
30-06-0150	<p>SPARE CIRCUIT - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Provide (1) spare 15-amp circuit.</p>	1.00
30-06-0175	<p>WIRING HARNESS CONNECTORS - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Connect all wiring harnesses via quick connect circular plug connectors.</p>	1.00
30-06-0300	<p>VOLTMETER - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Provide: (1) digital voltmeter on the master control console screen.</p>	1.00
30-06-0026	<p>WARNING DISPLAY - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Install: digital warning display integrated into the cab display console, programmed through the multiplex system to provide visual and audible indication.</p>	1.00
30-06-0225	<p>EMERGENCY MASTER SWITCH - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Supply: A single emergency master switch for activating all the emergency warning lights on the master control console screen, emergency master switch will activate the module power automatically, include an Emergency Master Menu button to allow access to individual warning light functions.</p>	1.00
30-06-0250	<p>CONTROL PANEL SWITCHES - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Switches on the master control console and attendant control panel screens shall have dimmable perimeter backlighting.</p>	1.00
30-06-0275	<p>MODULE POWER SWITCH - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Provide: A module power switch for the electrical system on both the Master Control Console and the Attendant Control Panel screens.</p>	1.00
30-06-0101	<p>ATTENDANT CONTROL PANEL (ACP) - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Attendant Control Panel (ACP) contains a color micro processor screen, controls all equipment installed in the patient compartment.</p>	1.00
30-06-0375	<p>PARK OVERRIDE - MULTIPLEX ELECTRICAL SYSTEM</p> <p>Park override switch on the master control console screen, reactivates all lights disabled when the transmission is placed in the neutral/park position.</p>	1.00
30-06-0400	<p>LOAD MANAGER-SEQUENTIAL SWITCHING SYSTEM - MULTIPLEX ELECTRIC SYSTEM</p>	1.00



	Load manager-sequential switching system controlled by the microprocessor based electrical system: emergency master button shall control the sequential switching of the emergency lights and/or other warning devices, load manager shall automatically shed non-critical electrical loads during low voltage conditions.	
30-06-0450	FRONT CLEAR DISABLE SWITCH - MULTIPLEX ELECTRICAL SYSTEM Activation of the switch on the master control console screen to disable all forward-facing clear warning lights.	1.00
30-06-0076	MASTER CONTROL CONSOLE (MCC) - MULTIPLEX ELECTRICAL SYSTEM Floor mounted Master Control Console (MCC) located in the cab, housing siren, color microprocessor display screen, controlling all the Emergency Warning functions, Patient Compartment lighting and module heat/ac functions.	1.00
30-06-0475	CURBSIDE SCENE LIGHTS ON WITH CURBSIDE DOOR The Curbside scene lights: programmed to activate when the Curbside door is in the open position.	1.00
30-06-0500	REAR SCENE LIGHTS ON WITH REAR DOORS OPEN Rear scene lights programmed to activate when the rear doors are in the open position.	1.00
30-06-0525	DISABLE SWITCH FOR REAR SCENE LIGHTS - MULTIPLEX ELECTRICAL SYSTEM Install: disable switch at the rear door area to disable the rear scene lights.	1.00
30-06-0550	DISABLE SWITCH FOR SIDE SCENE LIGHTS - MULTIPLEX ELECTRICAL SYSTEM A disable switch shall be installed at the curbside door area to disable the curbside scene lights.	1.00
30-06-0015	VISTA IV ACP - PUSH BUTTON Install: Weldon V-MUX Vista IV interface module / display screen mounted on an angled flip - down panel with chrome lever latches, in the patient compartment ACP area.	1.00
30-06-0010	VISTA IV MCC - PUSH BUTTON Install: Weldon V-MUX Vista IV interface module / display screen in the cab, operated through the use of push buttons.	1.00
30-10-0901	SYSTEM ACTIVE AND CHECK OUT LIGHTS - 15 MINUTES Switch: located at the curb and rear entry doors for activation of the V-MUX electrical system, check out light switch located at the curb and rear doors for activation of the left LED angled lights prior to entering the module, system programmed to shut down automatically after 15 minutes unless the ignition is on.	1.00
30-06-0050	DAYTIME RUNNING LAMPS - MULTIPLEX ELECTRICAL SYSTEM OEM Daytime Running Light headlights activated for daytime operation, when transmission is placed in drive.	1.00
30-10-0050	BATTERY CONVERTER - CHARGER Connect to Shoreline inlet: Progressive Dynamics #PD9245C, 45 amp, 125 VAC to 13.6 VDC converter, capable of maintaining the batteries when plugged in.	1.00



30-10-0071	CAMERA REAR VIEW - SINGLE SYSTEM - VISTA SCREEN Install: camera system rear view, tied to M-Tech display screen. Per Dwg #2. Camera alignment will be conducted at final inspection, if applicable.	1.00
30-10-0915	SYSTEM AUTO ACTIVE WITH ENTRY DOOR OPEN OR UNLOCK SIGNAL The system will auto activate when a module entry door is opened or when a door unlock signal is received.	1.00
30-10-0585	USB - DUAL OUTLET, ONE (1) INTERIOR LOCATED ON CONSOLE Install: (1) dual USB port outlet, 5 volt / 2.1 amp, in the vehicle, located on the Master Control Console in the cab.	1.00
USBAA101	OUTLET, USB - ONE (1) DUAL - PRIMARY ACTION AREA One (1) dual USB port outlet, 5 volt / 2.1 amp, shall be installed in the vehicle, located on the streetside primary action area in the patient compartment.	1.00
125AA101	OUTLET, 125VAC - ONE (1) INTERIOR DUPLEX - LEFT WALL ACTION AREA One (1) 2-wire +plus ground 125 VAC duplex outlet in the street side wall in the primary action area.	1.00
125AA201	OUTLET, 125VAC - ONE (1) INTERIOR DUPLEX - SECONDARY ACTION AREA One (1) 2-wire +plus ground 125 VAC duplex outlet in the street side wall in the secondary action area.	1.00
125IF201	OUTLET, 125VAC - ONE (1) INTERIOR DUPLEX - FRONT WALL CABINET One (1) 2-wire +plus ground 125 VAC duplex outlet in the front wall cabinet.	1.00
12VAA101	OUTLET, 12VDC - ONE (1) - LEFT WALL ACTION AREA One (1) 12 VDC power point outlet shall be installed in the street side wall in the primary action area. The outlet shall be labeled, "12 VDC". A Schottky diode medical isolator shall be provided to protect the 12 VDC outlet.	1.00
12VIF201	OUTLET, 12VDC - ONE (1) FRONT WALL - CABINET One (1) 12 VDC power point outlet shall be installed in the patient compartment, in the front wall cabinet. The outlet shall be labeled, "12 VDC". A Schottky diode medical isolator shall be provided to protect the 12 VDC outlet.	1.00
30-12-0001	RECEPTACLE SHORELINE INLET-SUPER 20 AMP, AUTO EJECT - YELLOW COVER Install: Kussmaul super auto eject shoreline inlet receptacle with yellow cover on module exterior (forward street side) near the driver's door, equipped with an integral dynamic disconnect.	1.00
30-10-0655	RADIO ANTENNA BASES - TWO (2) The coax cable(s) shall terminate in the cab behind the driver's seat. Two (2) antenna bases with attached coax cables shall be installed on the module roof. The coax cables shall terminate in the cab behind the driver's seat. Access to the antenna bases shall be through adjacent module interior dome lights.	1.00
30-10-0299	LIGHT, ATTENDANT CONTROL PANEL AREA - TECNIQ SILHO-X LED - WARM WHITE A Tecniq Silho-X 2.75" round warm white LED light with SS trim ring, shall be mounted above the left wall forward action area counter. The light shall be operated	1.00



	through a button on the ACP Vista screen labeled "Attendant Light". (Braun #26415)	
30-10-0310	LIGHT, LED ELECTRICAL COMPARTMENT -PDQ A 12 VDC LED light shall be located in the PDQ. The light shall be wired "battery-hot" to activate when the PDQ door is in the open position. The light shall be off when the door is in the closed position.	1.00
30-11-0106	LIGHTS, DOME LED (8) WHELEN SUPER LED Eight (8) Whelen #LED (80C0EHCR) dome lights, shall be installed. See dwg #9	1.00
30-11-0152	LIGHTS, RIDGEBACK LED PANEL (3) STREETSIDE - ANGLED Install: (3) Ridgeback LED lights streetside per dwg #5.	1.00
30-11-0176	LIGHTS, RIDGEBACK LED PANEL (2) CURBSIDE - ANGLED Install: (2) Ridgeback LED lights mounted on an angled panel above curbside seating area per dwg #6.	1.00
30-10-0410	LIGHTS, OSS COMPARTMENTS - INCANDESCENT Install: Truck-Lite brand incandescent lights, activated by magnetic switches. Compartments #1, #2, #3, and #4, each contain two (2) clear 4" round lights, and compartment #5 shall contain two (2) 2-1/2" clear round lights.	1.00
40-10-0191	LOCKS POWER - PASSAGE, 5 COMPARTMENTS, KEY FOBs Install: power door locks on module passage doors, and (5) OSS compartments, use OEM key fobs. Does not include battery bay door.	1.00
40-10-0151	SWITCH DOOR UNLOCK, WATERPROOF - HIDDEN IN FRONT GRILLE AREA Install: exterior hidden door unlock switch in grille area.	1.00
30-06-0201	RADIO TIE-IN POINT - (1) 12V/40 AMP - CAB CONSOLE AREA Install (1) set of 12 volt/40 amp radio tie-in studs in cab console: (1) battery hot, (1) ignition hot, (1) grounded stud.	1.00
30-06-0202	RADIO TIE-IN POINT - (1) 12V/40 AMP - PATIENT COMPARTMENT Install (1) set of 12 volt/40 amp radio tie-in studs in patient compartment: (1) battery hot, (1) ignition hot, (1) grounded stud.	1.00
30-06-0203	RADIO TIE-IN POINT - (1) 12V/250 AMP - PDQ Install (1) set of 12 volt/250 amp radio tie-in studs in the PDQ: (1) battery hot, (1) ignition hot, (1) grounded stud.	1.00

Braun - Exterior Lighting

Item Number	Description	Quantity
30-06-0410	WARNING LIGHTS FLASH PATTERN SIGNAL ALERT 75 - MULTIPLEX ELECTRICAL SYSTEM The default flash pattern for the vehicle warning lights: Signal Alert 75.	1.00
ClearLENS	CLEAR LENSES ON ALL WARNING LIGHTS	1.00
GWL050002	LIGHTS GRILLE - 2 WHELEN 500 SUPER LED	1.00



	Two (2) Whelen 500 series super LED warning lights, with waterproof connectors shall be installed the grille area of the chassis. The lights shall operate from a switch on the master control console labeled "Flashers".	
GWLC1R1R	GRILLE WARNING LIGHT LOCATION 1 - RED The warning light located on the grille in location 1 shall be red.	1.00
GWLC1R2R	GRILLE WARNING LIGHT LOCATION 2 - RED The warning light located on the grille in location 2 shall be red.	1.00
STRPTRN	STRAIGHT PATTERN WARNING LIGHTS The front warning lights will be aligned in a straight pattern across the module.	1.00
30-25-0122	LIGHTS, ICC / LED CLEARANCE - ON MODULE FRONT - TECNIQ Install: (5) amber Tecniq LED (S33-AA00-1) clearance / ICC lights on the front of the module near the roof line per dwg #1.	1.00
FWL090007	LIGHTS FRONT MODULE - 7 WHELEN 900 SUPER LED Seven (7) Whelen 900 series super LED warning lights with chrome bezels shall be installed on the module front. The lights shall operate from a switch on the master control console, labeled "Flashers".	1.00
FWLC1R1R	FRONT WARNING LIGHT LOCATION 1 - RED The warning light located on the upper front of the module in location 1 shall be red.	1.00
FWLC1R2R	FRONT WARNING LIGHT LOCATION 2 - RED The warning light located on the upper front of the module in location 2 shall be red.	1.00
FWLC1R3R	FRONT WARNING LIGHT LOCATION 3 - RED The warning light located on the upper front of the module in location 3 shall be red.	1.00
FWLC1R4W	FRONT WARNING LIGHT LOCATION 4 - WHITE The warning light located on the upper front of the module in location 4 shall be white.	1.00
FWLC1R5R	FRONT WARNING LIGHT LOCATION 5 - RED The warning light located on the upper front of the module in location 5 shall be red.	1.00
FWLC1R6R	FRONT WARNING LIGHT LOCATION 6 - RED The warning light located on the upper front of the module in location 6 shall be red.	1.00
FWLC1R7R	FRONT WARNING LIGHT LOCATION 7 - RED The warning light located on the upper front of the module in location 7 shall be red.	1.00
30-25-0123	LIGHTS, ICC / LED CLEARANCE - ON MODULE REAR - TECNIQ Install: (5) red TECNIQ LED (S33-RR00-1) clearance / ICC lights on the rear of the module near the roof line per dwg #2.	1.00
ROL090002	LIGHTS REAR MODULE, UPPER OUTER - 2 WHELEN 900 LED Two (2) Whelen 900 series super LED warning light with chrome bezels shall be installed on the upper rear of the module, in the outer location. The lights shall	1.00



	operate from a switch on the master control console, labeled "Flashers".	
ROLCLR1R	REAR OUTER MODULE LIGHT LOCATION 1 - RED The warning light located on upper rear of the module, in outer location 1 shall be red.	1.00
ROLCLR2R	REAR OUTER MODULE LIGHT LOCATION 2 - RED The warning light located on upper rear of the module, in outer location 2 shall be red.	1.00
RCL090001	LIGHTS REAR MODULE, UPPER CENTER - 1 WHELEN 900 LED One (1) Whelen 900 series super LED warning light with a chrome bezel shall be installed on the upper rear of the module, center location. The light shall operate from a switch on the master control console, labeled "Flashers".	1.00
RCLCLR1A	REAR CENTER MODULE LIGHT LOCATION 1-AMBER The warning light located on upper rear of the module in the center location shall be amber.	1.00
RS090002	LIGHTS REAR SCENE - 2 WHELEN 900 24 DIODE LED Two (2) Whelen 900 Series super LED scene/load lights with chrome bezels shall be installed on the upper rear of the module. The lights shall operate from a switch on the master control console, labeled "Rear Scene Lights".	1.00
WL090002	LIGHTS REAR WINDOW - 2 WHELEN 900 SUPER LED Two (2) Whelen 900 series super LED warning lights with chrome flanges shall be installed on the rear of the module at window level, one (1) on each side. These lights shall operate from a switch on the master control console, labeled "Flashers".	1.00
WLCLR1R	WINDOW LEVEL LIGHT LOCATION 1 - RED The warning light located on rear of the module at window level, location 1 shall be red.	1.00
WLCLR2R	WINDOW LEVEL LIGHT LOCATION 2 - RED The warning light located on rear of the module at window level, location 2 shall be red.	1.00
30-26-3009	LIGHTS, REAR TAIL - WHELEN 600 LED STOP, TURN, & MAXIMUM INTENSITY BACK-UP Install: (1) pair each of Whelen 600 series LED stop/tail lights, turn lights, and fully populated MAXIMUM intensity LED back-up lights with chrome bezels on rear of the module.	1.00
30-26-7002	LIGHT, LICENSE PLATE LED - WHELEN OACOEDCR Install:(1) Whelen OACOEDCR LED license plate light with 45 deg angled chrome-plated bezel on the rear of module, lower left side.	1.00
FIL07T0002	LIGHTS FRONT INTERSECTION - 2 WHELEN 700 LED W/15 DEGREE TILT HOUSING Two (2) Whelen 700 series super LED warning lights, with water-proof connectors, shall be mounted in 15 degree tilt housings on the front chassis fenders, one (1) on each side. The lights shall operate from a switch on the master control console labeled "Flashers". NOTE: When vehicle is placed in park, the override switch must be	1.00



	on for intersection light(s) to remain on.	
FILCLR1R	FRONT INTERSECTION LIGHT LOCATION 1 - RED The warning light located on front of the chassis fender in location 1 shall be red.	1.00
FILCLR2R	FRONT INTERSECTION LIGHT LOCATION 2 - RED The warning light located on front of the chassis fender in location 2 shall be red.	1.00
RIL070002	LIGHTS INTERSECTION REAR - 2 WHELEN 700 LED Two (2) Whelen 700 series super LED warning lights with, chrome flanges and water-proof connectors, shall be installed above the rear wheel wells, one (1) on each side. These lights shall operate from a switch on the master control console screen labeled "Flashers". NOTE: When vehicle is placed in park, the override switch must be on for intersection light(s) to remain on.	1.00
RILCLR1R	REAR INTERSECTION LIGHT LOCATION 1 - RED The warning light located on above the rear wheel well at location 1 shall be red.	1.00
RILCLR2R	REAR INTERSECTION LIGHT LOCATION 2 - RED The warning light located on above the rear wheel well at location 2 shall be red.	1.00
30-27-1102	LIGHTS, ICC / LED CLEARANCE - ON MODULE SIDE - TECNIQ Install: (2) red Tecniq LED (S33-RR00-1) clearance/ICC lights, (1) red on each side at rear of the vehicle, flash with turn signal, per Dwg #3 and #4.	1.00
SWL090004	LIGHTS SIDE WARNING - 4 WHELEN 900 SUPER LED Four (4) Whelen 900 series super LED warning lights with chrome flanges shall be installed, two (2) on each side of module exterior per dwg.	1.00
SWLCLR1R	SIDE WARNING LIGHT LOCATION 1 - RED The warning light located on side of the module, in outer location 1 shall be red.	1.00
SWLCLR2R	SIDE WARNING LIGHT LOCATION 2 - RED The warning light located on side of the module, in outer location 2 shall be red.	1.00
SWLCLR3R	SIDE WARNING LIGHT LOCATION 3 - RED The warning light located on side of the module, in outer location 3 shall be red.	1.00
SWLCLR4R	SIDE WARNING LIGHT LOCATION 4 - RED The warning light located on side of the module, in outer location 4 shall be red.	1.00
SS090004	LIGHTS SIDE SCENE - 4 WHELEN 900 24 DIODE LED Four (4) Whelen 900 series 24 Diode LED scene lights with chrome flanges shall be installed, two (2) each module side. These lights shall operate from switches on the master control console labeled "Left Scene Light" and "Right Scene Light".	1.00

Braun - Module Body Construction

Item Number	Description	Quantity
39-00-0005	AWS ALUMINUM CERTIFIED WELDERS	1.00



39-10-0005	<p>-----</p> <p>CONNECTIONS, CHASSIS TO MODULE</p> <p>Bolt: Module to the cab with (28) 5/16" grade 5 stainless steel bolts and nylock nuts evenly spaced along the sides and roof of the cab, weatherproof, double side adhesive foam tape seal installed between the module and cab, module body securely fastened to the chassis frame rail with (10) 12 mm bolts through rubber insulating spacers installed at (10) separate locations - (5 each frame rail), mounting bolts properly torqued and secured with locktite, system used for fastening the module to the chassis frame to be approved by the chassis manufacturer.</p> <p>-----</p>	1.00
40-00-0080	<p>-----</p> <p>INSULATION - POLYURETHANE SPRAY FOAM</p> <p>The walls, ceiling, passage doors, outside storage doors, the entire underside of the module floor (except for mounting pads), the underside of the outside storage compartments, the wheel wells, and the underside of the curbside step area shall be completely foam - in - place insulated with nominal 3/4" thick sprayed on Class I, urethane foam for thermal and aoustical insulation. The insulation shall comply with FMVSS #302 flame spread requirements. The underside of the body shall be properly prepared to ensure adhesion before the spray insulation is applied.</p> <p>-----</p>	1.00
39-00-0001	<p>-----</p> <p>MODULE BODY CONSTRUCTION - SEAMLESS</p> <p>Module: fabricated entirely of parts cut and formed from .125" (minimum) thickness 5052-H32 flat aluminum sheet stock, using CNC machines capable of .010" repeatability. This is the only alloy that may be used for body parts that are welded together. Roll-cage type interior super-structure, aluminum partition and module welded together into a single unit, roof designed with a minimum 1.5" crown to facilitate water run-off. Floor, roof, sides, all exterior doors fabricated from .125" (minimum) thick flat aluminum sheet stock, exterior joints between the roof and side components continuous full seam welded the entire length of the module. All exterior body panel joints continuous full seam welded. No VHB bonding tape or other adhesives used in the construction of the ambulance module.</p> <p>-----</p>	1.00
39-00-0002	<p>-----</p> <p>SOLE SOURCE MODULE BODY CONSTRUCTION</p> <p>-----</p>	1.00

Braun - Module Features / Exterior

Item Number	Description	Quantity
40-00-0009	<p>ALUMINUM PARTS - MODULE EXTERIOR</p> <p>All unpainted exterior aluminum parts to be bright dip anodized after fabrication to retain the finish and increase corrosion resistance.</p> <p>-----</p>	1.00
40-00-0010	<p>CORROSION MINIMIZATION - MODULE</p> <p>All module contact with dissimilar metals shall be minimized with the use of nylon screw-hole inserts to provide hinge to door isolation with the module body, polypropylene strip hinge isolation, polyethylene backed rubber tape, ceramic coated stainless steel hinge bolts, and ECK brand corrosion inhibitor spray.</p> <p>-----</p>	1.00
40-00-0020	<p>DOOR CONSTRUCTION - GASKET PLACEMENT</p>	1.00



All exterior hinged module doors shall be constructed in an inverted pan-formed design. The pan shall be constructed from .125" thick 5052-H32 flat sheet aluminum. The exterior door skin shall be constructed of .190" thick aluminum and welded to the pan. Door gaskets shall be attached to the interior side of the door skin on the top, bottom and outer edge of the door. The gasket on the hinge side of the door will be attached to the door frame.

40-00-0060	<p>EXTERIOR COMPARTMENTS - SWEEP-OUT</p> <p>Exterior module compartments: a sweep-out design to aid in facilitation of the purchaser's routine care and cleaning of the vehicle. All exterior compartment floors, with the exception of the front ALS compartment to be constructed to be flush with the bottom door frame.</p>	1.00
40-00-0030	<p>EXTERIOR COMPARTMENTS DESIGN</p> <p>All exterior compartments shall be vented and include: sound absorbing slip resistant polyurethane material sprayed on the inside of all compartments and compartment shelving, slide out trays and closeouts, baffled seep holes provided to prevent water from splashing or seeping into the exterior compartments, full-length, two-way adjustable, stainless steel hinges on all exterior compartment doors with 3/16" stainless steel hinge pins, compartment doors installed, flush with the module body, when double doors are provided, each door to have exterior handle, but only the forward door lockable, rearward door is secured when forward door is locked), all exterior compartments and passage doors keyed alike, lockable Eberhard "free-floating" type chrome plated handles with rotary locks. Gasket installed under each handle to protect the paint; drip rails installed above all exterior compartment doors.</p>	1.00
40-00-0050	<p>EXTERIOR COMPARTMENTS, VENTING</p> <p>(9) square inches (minimum) of venting inside #1, #2, #3, & #4 exterior storage compartments to provide for easier closure of the compartment doors.</p>	1.00
40-00-0055	<p>EXTERIOR COMPARTMENTS, VENTING - OXYGEN STORAGE</p> <p>(9) square inches (minimum) of venting provided in the exterior oxygen storage compartment, to dissipate any leaking oxygen gas.</p>	1.00
40-00-0070	<p>HANDLES, EBERHARD - CHROME FREE FLOATING TYPE</p> <p>Install: Eberhard #EMC-1-2110 chrome "free-floating" handles on each exterior module door, large enough to accommodate a gloved hand.</p>	1.00
40-10-0072	<p>LOWERED MODULE SIDES</p> <p>Module sides to be as low as possible and still comply with KKK-1822-F ramp break over angle.</p>	1.00
40-10-0320	<p>STEPWELL, CURBSIDE DOORWAY</p> <p>Install: aluminum diamond plate step well liner in curbside doorway step area.</p>	1.00
40-00-0090	<p>THRESHOLD, STAINLESS STEEL- EXTERIOR STORAGE COMPARTMENT</p> <p>Each exterior storage compartment with a hinged door (excluding battery compartment) to have stainless steel lower threshold at the door opening, protecting paint as equipment is installed and removed from the compartment.</p>	1.00
40-10-0340	<p>STONE GUARDS, MOD FRNT -ANODIZED DIAMOND PLATE</p>	1.00



	Install: anodized aluminum diamond plate stone guards on module front, (1) each side.	
40-10-0066	DOOR SLIDING - MODULE CURBSIDE PASSAGE Install EZ Glide curb door.	1.00
40-10-0088	DOORS - REAR PASSAGE Patient compartment rear door opening: doors flush without a protruding flange or lip, right rear passage door lockable, chrome exterior handle, left rear door non-locking, chrome exterior handle, all handles installed with a gasket, hinge full length stainless steel with a 3/16" stainless steel hinge pin, two-way adjustable, each rear door two-point slam action automotive type rotary latching system to the body, right rear door lock to the body at the top and bottom, not to left rear door, doors .213" steel door latch activator rods with clevis adjusters, doors lockable from inside and outside, shut on molded, air-core, automotive type door seals to prevent water from leaking into vehicle interior.	1.00
40-10-0130	EMERGENCY RELEASE LEVER, REAR PATIENT PASSAGE DOORS Install emergency release lever, attached to each rear passage door latch to be free-floating from the interior door linkages.	1.00
40-10-0505	WINDOWS, PASSAGE DOOR - (CURB SLIDING, REAR FIXED) Curbside passage door (sliding) window with removable screen, rear passage doors w/ non-openable window, windows 69% dark tint, secured with black oxide coated fasteners, open doors not to block warning lights.	1.00
40-10-0103	FENDERETTES - POLISHED ALUMINUM Install: Polished aluminum fenderettes around the rear wheel well openings.	1.00
40-10-0119	HOLD-OPEN - REAR DOORS - GRABBERS Install: door grabbers (1 pair) with hard rubber inserts on rear doors.	1.00
40-10-0360	KICKPLATE/THRESHOLD, REAR DOORWAY - ANODIZED DIAMOND PLATE Install: anodized aluminum diamond plate kick plate at the rear exterior doorway, providing a kick / scuff plate at rear of the vehicle above rear step, per dwg # 2.	1.00
40-10-0204	MUD FLAPS, REAR - BLACK RUBBER FIBERGLASS REINFORCED - THREE COLOR Install black rubber, fiberglass reinforced mud flaps with a minimum 1/4" thickness bolted to underside of module behind rear wheels, to provide adequate coverage of rear dual wheels of the chassis, mud flaps to be (3) color with the Manufacturers Logo.	1.00
40-10-0266	REAR STEP/BUMPER -FLIP-UP CENTER SECTION - STAR PUNCHED AND ANODIZED Affix: rear bumper to chassis frame, constructed with a hinged center section, (2) steel braces to secure step to chassis frame, outer 17" on each end of bumper constructed from heavy gauge stamped polished stainless steel bumper parts, to provide smooth rounded corners, step constructed of star punched .125" thick aluminum diamond plate, (2) rear LED step illumination lights provided. All diamond plate surfaces to be anodized; strip of black PVC installed on face of step.	1.00
40-10-0381	TOW HOOKS, MODULE REAR Secure: fasten (2) tow hooks in rear step area to rear step braces.	1.00
40-10-0280	RUB RAILS, ANODIZED ALUMINUM	1.00



	Install: anodized polished aluminum rub rails on lower sides of body, below outside compartment sill areas., rub rails to be offset 3/16" from body.	
40-00-0019	DOOR SKINS, OUTSIDE STORAGE COMPARTMENTS - DIAMOND PLATE INTERIOR SKINS Interior door skins for all outside storage compartments constructed of .063" thick aluminum diamond plate.	1.00
OS1XL3STD	OSS #1 - STREETSIDE FORWARD OSS #1 streetside forward, hinged door with spring-loaded gas cylinder, locking handle installed on the exterior of the door.	1.00
OS1XL3OP4	OSS #1 - OXYGEN STORAGE OSS #1 streetside forward, for housing an O2 cylinder.	1.00
OS102WELD	OSS #1 - OXYGEN STORAGE BRACKET WELDED IN FOR H or M CYLINDER An oxygen storage bracket shall be welded in OSS #1 for retention of "H" or "M" oxygen cylinders.	1.00
OS2XL3STD	OSS #2 - STREETSIDE CENTER OSS #2 streetside center, hinged double doors with spring-loaded gas cylinders, handles installed on the exterior of each door, forward door with locking handle.	1.00
OS2XL3OP1	OSS #2 - (1) ADJUSTABLE SHELF OSS #2 streetside center, with one (1) adjustable shelf.	1.00
OS2SHELF1	OSS #2 - SHELF ONE (1) ADJUSTABLE WITH TRACK Outside storage compartment #2 shall contain one (1) adjustable shelf with track.	1.00
OS3XL3STD	OSS #3 - STREETSIDE REAR - TALL DOOR OSS #3 streetside rear, hinged door with spring-loaded gas cylinder, locking handle installed on the exterior of the door.	1.00
OS3XL3OP1	OSS #3 - (1) ADJUSTABLE SHELF WITH INSIDE/OUTSIDE ACCESS OSS #3 streetside rear, for providing I/O storage access, and contain one (1) adjustable shelf.	1.00
OS3SHELF1	OSS #3 - SHELF ONE (1) ADJUSTABLE WITH TRACK Outside storage compartment #3 shall contain one (1) adjustable shelf with track.	1.00
OS4XL3STD	OSS #4 - CURBSIDE REAR OSS #4 curbside rear, hinged door with spring-loaded gas cylinder, locking handle installed on the exterior of the door.	1.00
OS4XL3OP4	OSS #4 - BACKBOARD AND (2) ADJUSTABLE SHELVES WITH INSIDE/OUTSIDE ACCESS AND FIXED DIVIDER OSS #4 curbside rear, with one (1) fixed vertical divider for backboard/scoop stretcher storage on one side and and two (2) adjustable shelves with inside/outside storage access on other.	1.00
OS4BB	OSS #4 - BACKBOARD - SCOOP STRETCHER STORAGE	1.00



	Compartment #4 shall provide storage for backboards / scoop stretcher, with a (1) inch adjustable strap with black plastic buckle.	
OS4DIV1	OSS #4 - FIXED DIVIDER One (1), fixed divider with sprayed on polyurethane material shall be provided and installed in outside storage compartment #4 per dwg. #4.	1.00
OS4SHELF2	OSS #4 - SHELVES TWO (2) ADJUSTABLE WITH TRACK Two (2) adjustable shelves with track in outside storage compartment #4.	1.00
OS5XL3STD	OSS #5 - CURBSIDE FORWARD OSS #5 curbside forward, hinged door with spring-loaded gas cylinder, locking handle installed on the exterior of the door.	1.00
OS5XL3OP1	OSS #5 - INSIDE/OUTSIDE ACCESS TO THE ALS CABINET OSS #5 curbside forward, inside/outside access to the ALS cabinet.	1.00
OS5XL3BAT	OSS #5 - CURBSIDE FORWARD DOOR WITH BATTERY COMPARTMENT Battery compartment located above the rubrail, on front curbside of the module, hinged on the forward edge, have a slide out tray, handle on the exterior of the door.	1.00

Braun - Module Interior / Patient Compartment

Item Number	Description	Quantity
50-51-1001	CABINET CONSTRUCTION - INTERIOR - ALUMINUM All interior cabinets shall be constructed of .090" thick welded aluminum.	1.00
50-60-0220	EMBLEMS / SIGNS - REAR PATIENT COMPARTMENT (2) "No Smoking / Oxygen Equipped / Fasten Seat Belts" signs: (1) sign installed in the cab, (1) above the oxygen outlets in the patient compartment street side cabinet.	1.00
50-60-0300	FLOOR CONSTRUCTION- PATIENT COMPARTMENT, NON-WOOD COMPOSITE Sub-floor in the patient compartment: constructed of .125" thick aluminum over .125" and .190" thick reinforcing hat sections and mounting laterals, aluminum sub-floor covered with a 3/4" non-wood composite material, all corner molding, edging and trim anodized aluminum or stainless steel and sealed to prevent fluids from seeping under the cabinets.	1.00
50-60-0301	FLOORING - COVE Patient compartment floor radius: coved with pre-formed floor coving material, installed behind the vinyl floor covering, along both the street side and curbside walls.	1.00
50-60-0391	HEADLINER - REAR PATIENT COMPARTMENT Headliner in the patient compartment shall be one-piece, seamless, .090 thick aluminum finished with sprayed-on multi-use polychromatic coating.	1.00
50-51-1013	HOLD OPENS FOR INTERIOR DOORS	1.00



	All interior cabinets with doors less than 6" tall shall have friction hinges as hold opens for door(s). Doors 6" and taller shall be designed using gas shocks as hold opens for the door(s).	
50-60-0660	PADDED EDGING PROTECTION Install: padded corner edging where necessary on exposed corners and edges in the patient compartment for patient and attendant protection.	1.00
50-00-0202	ROUNDED INTERIOR CORNERS Interior vertical edges: rounded/padded corners in the following locations: forward and aft edges of the CPR seat, the wall at the aft end of the squad bench, the partition opening cabinet edges and the upper front wall cabinet.	1.00
50-51-1011	RECESSED ADJUSTABLE SHELF TRACK - CABINETS Install recessed adjustable shelf track in cabinets.	1.00
50-51-5001	UPHOLSTERY - PATRIOT PLUS CHARCOAL #8605 All cushions, head pads and seating surfaces shall be covered with Patriot Plus Charcoal #8605	1.00
50-60-0661	INTERIOR MODULE PADS Vinyl upholstered, foam cushioned head/back pads shall be installed as follows: the lower edge of the upper front wall cabinet (above the partition doorway or window), above the rear doors, above the side door, and on the street side wall behind and on each side of the CPR seat. The pads shall be covered with a flame-retardant color coordinated vinyl upholstery material.	1.00
50-51-6003	LONPLATE II, NON-SLIP EMBOSSED SM. GRID - GUNMETAL #424 The floor in the patient compartment shall be covered with Lonseal brand "Lonplate II" non-slip; small grid (embossed) Gunmetal #424.	1.00
50-51-2002	CABINET DOORS - CLEAR POLYCARBONATE All cabinet doors shall be clear polycarbonate material / installed in aluminum track lined with PPL inserts / An edge mounted aluminum handle shall be installed on each sliding cabinet door.	1.00
50-51-3001	CABINETS/ WALLS - POLYCHROMATIC COATING - MARBLE STONE Headliner, walls, cabinet faces, and cabinet interiors MultiSpec color to be Marble Stone	1.00
IS-CNT2-ACR	COUNTER TOP, SOLID ACRYLIC - SECONDARY ACTION AREA Install: solid acrylic countertop with 1/2" lip on the secondary action area.	1.00
IS-CNT-ACR	COUNTER TOP, SOLID ACRYLIC Install: solid acrylic countertop with 1/2" lip on the primary action area.	1.00
50-51-4033	COUNTERTOP - SOLID ACRYLIC - RAVEN BOULDER (GRAY/BLACK) Install a solid acrylic counter top, Raven Boulder (#810).	1.00
50-01-0408	LATCHES, CABINET, CN10 COMPLIANT AS APPLICABLE - INCLUDING RADIO CABINET The ACP (attendant control panel) door, the PDQ (power distribution quarters) door, and the radio cabinet door shall	1.00



	be secured with chrome locking lever latches/ all remaining interior hinged cabinet doors with center squeeze latches/all interior drawers with locking flush pull latches.	
50-10-0229	LEFT WALL - ATTENDANT CONTROL PANEL - WITH FLAT AREA A Weldon Vista Control Screen shall be mounted on a hinged access panel and secured with two (2) latches. The panel will be located to the immediate right of the attendant's seat. The forward portion of the panel will contain a flat area that may be used for future radio mounting, etc.	1.00
IS1XL3OP1	CABINET - FIXED FRAME WITH SLIDING POLYCARBONATE DOORS AND (1) ADJ. SHELF EACH SIDE OF CENTER DIVIDER Left wall, upper rear interior cabinet (#1): fixed frame, sliding polycarbonate doors w/full length handles, the outer most sliding door to have handles on both ends, center divider with (1) adjustable shelf each side	1.00
IS2XL3OP1	CABINET - FIXED FRAME WITH SLIDING POLYCARBONATE DOORS AND (1) ADJ. SHELF EACH SIDE OF CENTER DIVIDER Left wall, upper interior cabinet (#2): fixed frame, sliding polycarbonate doors w/full length handles, the outer most sliding door to have handles on both ends, center divider with (1) adjustable shelf, each side.	1.00
IS3XL3OP1	CABINET - HINGED POLYCARBONATE DOORS WITH CENTER SQUEEZE LATCHES AND FULL LENGTH HANDLES, INSIDE/OUTSIDE ACCESS TO OSS #3 Left wall rear interior cabinet (#3): fixed frame, hinged polycarbonate doors w/center squeeze latches and full length handles, inside/outside access to OSS #3.	1.00
IS4XL3OP1	CABINET - SLIDING POLYCARBONATE DOORS WITH (1) ADJUSTABLE SHELF Left wall interior cabinet (#4) below secondary action area: fixed frame, sliding polycarbonate doors w/ full length handles, the outermost sliding door to have handles on both ends (1) adjustable shelf.	1.00
IS5XL3OP1	PULL-OUT DRAWER WITH HINGED ACRYLIC WRITING SURFACE AND LOCKING STAINLESS STEEL FLUSH PULL LATCH. RECESSED SUCTION BELOW DRAWER Left lower wall: (1) drawer (#5) aisle facing, primary action area, under the attendant control panel, hinged acrylic writing surface, locking stainless steel flush pull latch. A recessed SSCOR suction canister shall be located below the drawer. An SSCOR suction system with a 12 VDC electric vacuum pump: recessed into the street side lower interior wall near the attendant seat, pump shall be mounted in the standard OSS #2, pump exhaust shall be vented to the exterior of the vehicle. (must use SSCOR pump and tubing)	1.00
50-60-0018	ASPIRATOR / SUCTION - SSCOR - WITH ELECTRIC PUMP - RECESSED An SSCOR suction system shall be recessed into the street side lower interior wall near the attendant's seat. The 12 VDC SSCOR electric vacuum pump to be installed in an exterior compartment per the location on the drawing (must use SSCOR pump and tubing).	1.00
IC1XL3OP2	INSIDE/OUTSIDE ACCESS TO OSS #4 WITH HINGED POLYCARBONATE DOOR, FULL LENGTH HANDLE, AND CENTER SQUEEZE LATCH Compartment #1 on the rearward curb side wall, inside/outside access to OSS #4, hinged polycarbonate door, full length handle, center squeeze latch.	1.00



IC2XL3OP22	SQUAD BENCH WITH RECESSED SHARPS/WASTE BELOW SEPARATE BENCH LID. SECOND PATIENT TRANSPORT ON THE SQUAD BENCH. The Curbside wall shall have a squad bench which will include storage, a split lid with gas cylinder hold opens, and a recessed sharps and trash container.	1.00
IC3XL3OP1	(2) ANGLED LED LIGHTS OVERHEAD (2) LED lights on overhead angled panel on curb side upper wall.	1.00
50-50-0503	SQUAD BENCH TOP - SPLIT WITH HINGED LID FORWARD WITH SHARPS / TRASH ACCESS Squad bench top and cushion shall be split into two (2) sections with separate hinged lids/ forward most section shall have the sharps and trash container installed/ bench covered with color coordinated vinyl upholstery material/automatic latching fastener shall be installed in both sections	1.00
50-50-0541	HOLD OPENS - SQUAD BENCH LID - GAS CYLINDERS Gas cylinder hold-open(s) shall be provided and installed to hold lid in the open and closed position.	1.00
50-60-0709	SHARPS AND TRASH CONTAINERS - ACCESS THRU SQUAD BENCH LID A 6.9 qt. #BD5489 sharps container, and a 8 qt. trash container installed in the forward end of the squad bench base, containers accessed through the squad bench lid covered with a 3/8" thick clear acrylic hinged lid with a biohazard warning label.	1.00
50-60-0718	SQUAD BENCH FACE - VINYL FLOORING MATERIAL The face of the squad bench shall be covered with vinyl flooring material.	1.00
SQ-BN-BASE	SQUAD BENCH BASE W/STORAGE A storage area shall be provided in the squad bench base. The squad bench base shall be constructed of .090" thick aluminum for maximum storage capacity and minimum weight. The interior of the squad bench shall be sprayed with sound absorbing polyurethane material.	1.00
IF3PDQ	CABINET - PDQ The Power Distribution Quarters (PDQ) shall hold electrical components, (i.e., power distribution nodes, circuit breakers, etc.), hinged door with (2) chrome locking lever latches, located on the partition wall behind the attendant seat.	1.00
IF1XL3C4	CABINET - FRONT WALL, UPPER #1 - HINGED ALUMINUM DOOR W/INSERT The front wall interior cabinet #1: fixed frame, flip up hinged aluminum door with polycarbonate insert and gas shock hold-open(s), center squeeze latch, (1) adjustable shelf	1.00
IF1XL3OP4	CABINET WITH HINGED ALUMINUM DOOR WITH POLYCARBONATE INSERT AND CENTER SQUEEZE LATCH WITH (1) ADJUSTABLE SHELF Install cabinet with hinged aluminum door and gas shock hold-open(s), polycarbonate insert in upper front wall.	1.00
IF2XL3OP1	CABINET - UPPER/LOWER WITH HINGED POLYCARBONATE DOORS, CENTER SQUEEZE LATCHES, (1) ADJ. SHELF PER CABINET Interior front wall cabinet #2: fixed frame, separated into (2) cabinet sections, each enclosed by one (1) set of hinged polycarbonate doors, each section center squeeze	1.00



	latches,(1) adjustable shelf per each section and (1) adjustable shelf between the sections for a total of (3) adjustable shelves.	
IF3XL3OP1	CABINET - VENTED RADIO CABINET WITH PDQ ABOVE Power Distribution Quarters (PDQ) compartment and a vented radio compartment below the PDQ, located in front wall, left.	1.00
IF3XL3RAD	CABINET - FRONT WALL, LOWER BELOW PDQ (SINGLE VENTED DOOR) A radio cabinet with a vented, hinged aluminum door, secured by a chrome locking lever latch, located on the front lower left wall, door to open towards rear of the module.	1.00
IF4XL3OP1	WALK-THROUGH OPENING WITH HINGED DOOR The front wall shall have a walk-through opening with a hinged door with window.	1.00
50-20-0505	PARTITION DOORWAY - WITH HINGED DOOR A walk-through doorway: between the cab and patient compartment, doorway extend from the floor to the cab headliner, hinged door provided for the walk-through partition, door only be opened and closed from the cab side to provide maximum security, door in the open position- recessed into the side of the lower front wall cabinet, door automatically secured while in the open or closed positions, w/ window with a minimum of 150 square inches of viewing area - located to enable the driver to view into the patient compartment, and to minimize glare from the rear dome lights.	1.00
50-50-0118	SEATING - ATTENDANT - USSC VALOR R - BACK INTEGRAL CHILD, SWIVEL SEAT CN8 COMPLIANT A USSC Valor rear facing, R-back attendant seat with an integrated child seat installed at the head of the patient cot: a (2) position swivel seat mounted on a pedestal base with a heavy-duty seat frame / ABTS (All Belts To Seat) application with (4) point / (4) retractors single click internal mount belt system. The seat shall be padded and covered with sewn matching vinyl upholstery.	1.00
50-50-0122	SEATING - ATTENDANT - SIDE MOUNT POSITION The attendant seat shall be in a side mount position.	1.00
CPROP1	SEATING - CPR - VALOR WITH 4PT BELTING A CPR seat: on the street side of the patient compartment aft of the primary action area counter: KKK-A-1822F Change Notice 8 compliant, VALOR A-VAL shelf mount back frame and internal bolsters, single click, four (4) point / four (4) retractors, internal mount belt system, VALOR A-VAL shelf mount back frame and the seat shall be padded and covered with cushioned, color coordinated, cut and sewn vinyl.	1.00
SQSTOP1	SEATING - CN8 COMPLIANT TWO (2) VALOR A-VAL BACK A Squad bench seat: (2) Valor A-Val Back individual seating positions will be installed on the curb side of the patient compartment. Seats shall have a VALOR A-VAL shelf mount back frame and internal bolsters with (4) point / (4) retractors single click internal mount belt system / padded and covered with cushioned, color coordinated, cut and sewn vinyl.	1.00
50-60-0424	HEAT/AIR CONDITIONING, HOSELINE FT-454, BRUSHLESS BLOWER 580 cfm (36,000 BTU HEAT/32,000 BTU COOL)	1.00



	Install Hoseline FT-454 with 4x4 AC/Heat Core w/ brushless blower motor.	
50-61-0001	ASSIST HANDLES, (6) BLACK RUBBER Install: a total of (6) 10-7/8" black vulcanized rubber with steel core assist handles installed: (1) handle on each rear door, (1) on the curbside door, (1) at the curbside doorway and (2) at the rear doorway.	1.00
50-60-0730	DOOR PANELS - MODULE PASSAGE DOORS - FULL LENGTH ALUMINUM - W/ACCESS PANELS Interior rear and curbside passage door panels to be full length aluminum, Multi-Spec sprayed to match interior color and contain removable latch access panel per dwg. # 6 & # 8. (Total 3).	1.00
50-60-0256	EXHAUST VENTILATOR, 3-SPEED - MULTIPLEX ELECTRIC SYSTEM Install: three-speed, 250 CFM (minimum) exhaust fan in the street side cabinet in the patient compartment, fan pulse width modulated from a switch on the attendant control panel vista screen, exhaust system to have a louvered grille inside and a chrome vent outside, system vent through the side of the vehicle, not through the roof.	1.00
50-60-0322	GLOVE DISPENSER - (3) BOX - ABOVE ENTRY DOOR - CURBSIDE (ABS) A three (3) - box glove dispenser unit, with a clear acrylic hinged access panel with three (3) cut-outs, shall be provided above the curbside entry door. A 1/4" turn latch will be installed on the face of the glove box access panel.	1.00
50-60-0340	GRAB RAIL, 1-1/4" DIAMETER, (96") OVER COT AREA (1) 1-1/4" diameter x 96" long stainless steel grab rail installed on the ceiling for attendant/ patient balance control, attached to the ceiling with (3) mounting brackets that secure it to the super structure of the module. Installation to comply with AMD-008 requirements.	1.00
50-60-0431	IV HANGERS - CEILING RECESSED - CAST PRODUCTS #IV2008-1 (2) Two (2) Cast Products #IV2008-1 recessed; dual ceiling I.V. hangers shall be provided per Dwg #9 locations.	1.00
50-60-0640	OXYGEN SYSTEM, ELECTRIC - MULTIPLEX ELECTRIC SYSTEM A 12 VDC controlled electric O2 system operated through the v-mux multiplex electrical system shall be provided and installed.	1.00
50-60-1601	OXYGEN OUTLET (1) LEFT WALL - OHIO MED - ACTION AREA One (1) Ohio Medical flush mounted; quick release wall outlet shall be installed in the forward street side cabinet action area. Per dwg #5	1.00
50-60-1640	OXYGEN OUTLET (1) RIGHT WALL - OHIO MED - HEAD END OF SEATING AREA One (1) Ohio Medical flush mounted; quick release wall outlet shall be installed in the right wall above the head end of the curbside seating area. Per dwg #6	1.00
50-60-1680	OXYGEN OUTLET (1) CEILING - OHIO MED - ABOVE HEAD OF COT One (1) Ohio Medical flush mounted; quick release oxygen outlet shall be installed in the ceiling above the head of cot in the center mount position. Per dwg #9	1.00
50-60-0629	FLOW METER, OXYGEN - THORPE STYLE	1.00



	One (1) Thorpe style oxygen flow meter (15LPM) shipped loose with the completed vehicle.	
50-60-0761	STAINLESS STEEL WALL PROTECTION - INTERIOR STREETSIDE A brushed stainless steel panel shall be provided on the street side wall from the bottom of the CPR seat.	1.00
50-60-0820	ANTI-SLIP MATTING - CURBSIDE STEPWELL Anti-Slip charcoal gray matting shall be installed in the curbside step well.	1.00

Braun - Optional Patient Compartment Items

<i>Item Number</i>	<i>Description</i>	<i>Quantity</i>
50-62-0302	COT FASTENER - STAT-TRAC SINGLE - CENTER POSITION CN8 COMPLIANT Install a 96" Stat-Trac single position center mount	1.00

Braun - Paint / Graphics

<i>Item Number</i>	<i>Description</i>	<i>Quantity</i>
60-01-0001	PAINT PROCEDURE All non-anodized aluminum module body surfaces: completely chemically steam cleaned, filled with premium body filler as needed, sanded smooth and primed with an epoxy primer and then primed again with a high solid primer, cured primer surfacer shall be DA sanded with 320 grit and cleaned. A high solid primer shall then be applied, where needed, as a sealer.	1.00
60-01-0005	STANDARDS AND SPECIFICATIONS FOR VEHICLE PAINT APPEARANCE Adhere to Standards and Specifications for Vehicle Paint Appearance.	1.00
60-10-0107	CAB - OEM PAINT White	1.00
60-01-0004	BUFFING, PAINT - MODULE The paint on the module sides shall be buffed to a high shine using a recommended paint buff system.	1.00
60-01-0006	PAINT MODULE - OEM PAINT PLUS CLEAR COAT White Module shall be painted OEM, also be clear-coated, using an Axalta Process, sprayed over the final paint coat.	1.00
60-30-0200	REFLECTIVE - DOOR REFLECTIVITY Install reflective material (25" x 2.5" red/silver chevron style), on the lower interior stainless steel panel of each rear door and hinged side door. NOTE: If a sliding side door is provided, install a 1.50" x 40.00" white reflective stripe on the rear facing edge.	1.00
60-25-0101	REFLECTIVE - BLACK MATERIAL IN RUB RAILS	1.00



Install black reflective material in rub rails.

Braun - Vehicle Manuals

<i>Item Number</i>	<i>Description</i>	<i>Quantity</i>
80-20-0001	VEHICLE MANUALS (1) PACKAGE SET One (1) Delivery Manual Package shall be supplied with the vehicle, and shall include the following items: Ambulance manufacturer parts, service, and operation manuals, OEM chassis owner's guide, complete 12 VDC and 125 VAC wiring schematics for all included standard and optional systems, Multiplex Electrical system programming - electronic media -----	1.00
90-10-0007	STATEMENT OF LIMITED WARRANTY NEW AMBULANCES -----	1.00

FORD GAS CUTAWAY		E450
Level	DESCRIPTION	158 GAS E4F
1	FORD GAS V8 C/W E450 158 WHT US	
1	Destination & delivery	DEST.
1	Preferred Equipment Package	782A
1	7.3L V8 Premium engine	99N
1	6-Speed O/D w/Tow Haul transmission	44P
1	Wheelbase	158
1	Oxford White CC	YZ
1	Cloth Captains Chairs	M
1	Medium Flint	E
1	Max. Payload 8290 lbs GVWR 14500 lbs	20F
1	Ext. Upg. Package	18A
2	<i>Front chrome bumper</i>	764
2	<i>Chrome grille</i>	INCL
1	Int. Upg Package CUT	18C
*1	Dual Cloth Captain's Chairs	21A
2	<i>Front cloth headliner</i>	INCL
2	<i>High-series door-trim panels</i>	INCL
2	<i>Floor covering – front, black vinyl</i>	INCL
2	<i>Cloth sun visors</i>	INCL
2	<i>Power door-locks and windows</i>	903
2	<i>Insulation Package</i>	552
1	Amb. Prep. Package Gas	47H
2	<i>Dual 78 amp-hr heavy-duty batteries</i>	634
2	<i>Auxiliary Heater – Air Conditioning Connector Package</i>	57L
2	<i>Auxiliary Fuel Port</i>	945
2	<i>Limited-Slip Axle</i>	INCL
2	<i>Alternator – 240 amp</i>	63O
2	<i>Front Max GAWR</i>	INCL
2	<i>Spare Tire and Wheel</i>	51A
2	<i>Mirrors, Telescoping Trailer Tow with Manual Adjustments</i>	54D
2	<i>Vinyl headliner and sun visors</i>	INCL
2	<i>Two (2) exhaust heat shields mounted in mid-chassis right-hand</i>	INCL
2	<i>License plate bracket</i>	INCL
2	<i>Badging (shipped in dunnage)</i>	INCL
1	Driver Assist Technology Package	526
2	<i>Automatic Emergency Braking (AEB),</i>	INCL
2	<i>Distance Alert/Distance Indication</i>	INCL
2	<i>Post-Collision Braking</i>	INCL
2	<i>Adaptive Cruise Control</i>	INCL
2	<i>Lane Departure Warning Driver</i>	INCL
2	<i>Alert System and Auto-High Beam Control</i>	INCL
2	<i>Instrument Panel Electronic Message Center</i>	60J
1	Frame pucks (isolators)	559
1	Mirrors, Telescopic Trailer Tow Mirrors Power	54E
1	Interior rearview mirror day/night	625
*1	Programmable Daytime running lamp	INCL
1	Remote keyless entry	948
1	4 speakers	874

1	Engine Console Cover Delete	41X
1	Engine block heater	41H
1	Vinyl floor covering	162
1	B-Pillar Trim Kit	92B
1	Fuel charge	693
1	NET INV FLT OPT	B4A
STD	<i>Dual airbags - 2nd generation</i>	<i>596</i>
1	LT225/75Rx16E BSW A/S – DRW	T68
1	Passenger Airbag Cutoff Switch	62C
*1	50 State Emissions	425
*1	Bluetooth-capable AM/FM stereo w/clock display USB input	587
*1	Front License Plate Bracket	153
1	Daytime running lights * new 2023	942
STD	<i>208 Litres (55 gallon) opt only on E-350 DRW 158"</i>	<i>656</i>
STD	<i>Horn – dual-note</i>	<i>INCL</i>
STD	<i>Air conditioning front only</i>	<i>INCL</i>
STD	<i>16" x 6" Painted White Steel Wheels – DRW only</i>	<i>646</i>
STD	<i>Dual Airbags – 2nd Generation</i>	<i>INCL</i>
STD	<i>Electronic Stability Control (ESC)</i>	<i>INCL</i>
STD	<i>Safety Belts – Medium Flint w/height-adjustable D-ring</i>	<i>INCL</i>
STD	<i>Traction Control</i>	<i>INCL</i>
STD	<i>Hill Start Assist</i>	<i>INCL</i>
STD	<i>Air conditioning - front only</i>	<i>STD</i>
STD	<i>Courtesy light switch, front-door</i>	<i>STD</i>
STD	<i>Dash sound absorber</i>	<i>STD</i>
STD	<i>Dome light - front</i>	<i>STD</i>
STD	<i>Engine cover console - slim line colour-keyed w/dual bin stowage</i>	<i>STD</i>
STD	<i>Glove box w/aux powerpoint</i>	<i>STD</i>
STD	<i>Grab handles - A-pilar</i>	<i>STD</i>
STD	<i>Horn dual-note</i>	<i>STD</i>
STD	<i>Instrument panel - medium flint</i>	<i>STD</i>
STD	<i>Key-in-ignition warning chime</i>	<i>STD</i>
STD	<i>LH/RH black cowl trim panels (marche pied d'entrée par Robin)</i>	<i>STD</i>
STD	<i>Light & convenience group</i>	<i>STD</i>
STD	<i>Modified vehicle wiring kit & system</i>	<i>STD</i>
STD	<i>Powerpoint 12V in I/P</i>	<i>STD</i>
STD	<i>Steering gear - HD</i>	<i>STD</i>
STD	<i>Steering wheel - tilt</i>	<i>STD</i>
STD	<i>Tachometer</i>	<i>STD</i>
STD	<i>Stabilizer bar - front w/heavy-duty front & rear shocks</i>	<i>STD</i>
STD	<i>Steel valve stems</i>	<i>STD</i>
STD	<i>Brakes - 4 wheel disc ABS</i>	<i>STD</i>
STD	<i>Electronic throttle control (ETC)</i>	<i>STD</i>
STD	<i>Shock absorbers - HD gas</i>	<i>STD</i>
STD	<i>Safety belts - colour keyed w/height-ajustable D-ring</i>	<i>STD</i>

Engine cooling

Transmission cooler

Power steering

Anti-lock brakes

Factory tint

86" wide minimum mirrors

Multi-speed wipers with intermittent

Spare tire, Jack and wrench